

Material Safety Data Sheet

Revision Date: 08/08/2013
Z17000000388/Version: 2.1
Print Date: 04/08/2015
Page: 1/8



1. Identification of the substance/mixture and of the company/undertaking

Product name: KODAK EKTACOLOR SMPU P2/RA-2SM KIT, Part A

Product code: 1701325 - Part A

Supplier: Kodak Alaris Inc., 2400 Mount Read Boulevard, Rochester, NY 14615

IN EMERGENCY, telephone: 1-800-424-9300 or +1 703-527-3887.

For further information about this product, email EHS-Questions@Kodakalaris.com.

Synonyms: PCD 4566

Product Use: photographic processing chemical (bleach/bleach fixer), For industrial use only.

2. Hazards identification

CONTAINS: Ammonium thiosulphate (7783-18-8), Sodium bisulphite (7631-90-5), Ammonium bisulphite (10192-30-0), Ammonium acetate (631-61-8)

WARNING!

MAY BE HARMFUL IF SWALLOWED

CAUSES EYE IRRITATION

DRIED PRODUCT RESIDUE CAN ACT AS A REDUCING AGENT

HMIS III Hazard Ratings: Health - 2, Flammability - 1, Physical Hazard - 1

NFPA Hazard Ratings: Health - 3, Flammability - 1, Instability - 0

NOTE: HMIS III and NFPA 704 (2007) hazard indexes involve data review and interpretation that may vary among companies. They are intended only for rapid, general identification of the magnitude of the potential hazards. To adequately address safe handling, ALL information in this MSDS must be considered.

3. Composition/information on ingredients

Weight percent	Components - (CAS-No.)
45 - 50	Ammonium thiosulphate (7783-18-8)
5 - 10	Sodium bisulphite (7631-90-5)
1 - 5	Ammonium bisulphite (10192-30-0)

Material Safety Data Sheet

Revision Date: 08/08/2013

Z17000000388/Version: 2.1

Print Date: 04/08/2015

Page: 2/8

1 - 5 Ammonium acetate (631-61-8)

0.1 - 1 Acetic acid (64-19-7)

4. First aid measures

Inhalation: If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention.

Skin: Wash off with soap and water. Get medical attention if symptoms occur.

Ingestion: If swallowed, DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control centre immediately.

5. Fire-fighting measures

Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Flush with plenty of water.

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Fire or excessive heat may produce hazardous decomposition products.

Hazardous Combustion Products: Carbon oxides, nitrogen oxides (NO_x), Sulphur oxides, (see also Hazardous Decomposition Products sections.)

Unusual Fire and Explosion Hazards: Dried product residue can act as a reducing agent. Reacts violently with oxidizing materials. May cause spontaneous heating and ignition when absorbed on combustible, porous material (e.g. rags, paper, sawdust, cotton, clothing).

6. Accidental release measures

Absorb spill with vermiculite or other inert material. Collect in a noncombustible container for prompt disposal. Clean surface thoroughly to remove residual contamination.

For Large Spills: Flush with plenty of water.

7. Handling and storage

Personal precautions: Avoid breathing mist or vapour at concentrations greater than the exposure limits. Avoid contact with eyes, skin, and clothing. Use only with adequate ventilation. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.

Material Safety Data Sheet

Revision Date: 08/08/2013

Z17000000388/Version: 2.1

Print Date: 04/08/2015

Page: 3/8

Prevention of Fire and Explosion: Keep from contact with oxidizing materials, highly oxygenated or halogenated solvents, organic compounds containing reducible functional groups. Remove and wash contaminated clothing promptly.

Storage: Store in original container. Keep container tightly closed to prevent the loss of water. Keep away from incompatible substances (see Incompatibility section.) Store in a well-ventilated place. Keep cool.

8. Exposure controls/personal protection

Occupational exposure controls

Chemical Name	Regulatory List	Value Type	Value
Sodium bisulphite	ACGIH	time weighted average	5 mg/m3
Sulphur dioxide		Short term exposure limit	0.25 ppm
	OSHA	time weighted average	5 ppm 13 mg/m3

Ventilation: Good general ventilation should be used. Ventilation should be sufficient so that applicable occupational exposure limits are not exceeded. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances.

Respiratory protection: None should be needed. A respirator should be worn if hazardous decomposition products are likely to be or have been released. Respirator type: acid gas If respirators are used, a program should be instituted to assure compliance with applicable federal, state, commonwealth, provincial, or local laws and regulations.

Eye protection: Wear safety glasses with side shields (or goggles).

Hand protection: For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

9. Physical and chemical properties

Physical form: liquid

Colour: clear light yellow

Odour: slight sulphur dioxide

Specific gravity: 1.32

Vapour pressure (at 20.0 °C (68.0 °F)) : 24 mbar (18.0 mm Hg)

Vapour density: 0.6

Material Safety Data Sheet

Revision Date: 08/08/2013

Z17000000388/Version: 2.1

Print Date: 04/08/2015

Page: 4/8

Boiling point/boiling range: > 100 °C (> 212.0 °F)

Water solubility: complete

pH: 5.4

Flash point: does not flash

10. Stability and reactivity

Stability: Stable under normal conditions.

Incompatibility: Acids, Strong bases, sodium hypochlorite (bleach), Halogenated compounds, Oxidizing agents. Contact with sodium hypochlorite (bleach) may form chloramine (toxic gas). Contact with base liberates flammable material. Contact with strong acids liberates sulphur dioxide. Contact with base liberates ammonia.

Hazardous decomposition products: Ammonia, chloramine, Sulphur oxides, nitrogen oxides (NO_x)

Hazardous Polymerization: Hazardous polymerisation does not occur.

11. Toxicological information

Effects of Exposure

General advice:

Contains: Acetic acid. Acute overexposure to extremely high airborne concentrations of respiratory irritants has been associated with development of an asthma-like reactive airways syndrome (RADS) in susceptible individuals. Extremely high airborne concentrations are not generated during normal conditions of use but may occur following a spill. The potential to generate extremely high airborne concentrations in a spill situation depends upon physical factors such as the concentration of the solution, the volume of the spill, the surface area of the spill, the size of the room where the spill occurred, and the ventilation rate in the room.

Inhalation: Expected to be a low hazard for recommended handling. Some asthmatics or hypersensitive individuals may experience difficulty breathing if exposed to aerosols or decomposition products that are not anticipated during normal use.

Eyes: Causes eye irritation.

Skin: This material has a low potential to cause allergic skin reactions; however, cases of human skin sensitization have been reported.

Material Safety Data Sheet

Revision Date: 08/08/2013
Z17000000388/Version: 2.1
Print Date: 04/08/2015
Page: 5/8

Ingestion: May be harmful if swallowed. Some asthmatics or sulfite-sensitive individuals may experience wheezing, chest tightness, stomach upset, hives, faintness, weakness and diarrhea.

Data for Ammonium thiosulphate (CAS 7783-18-8):

Acute Toxicity Data:

Oral LD50 (male rat): 500 - 5,000 mg/kg

- Eye irritation: none

Data for Sodium bisulphite (CAS 7631-90-5):

Acute Toxicity Data:

Oral LD50 (rat): > 1,600 mg/kg

- Dermal LD50 (rat): 2,000 mg/kg
- Eye irritation (May irritate eyes.): mild

Data for Acetic acid (CAS 64-19-7):

Acute Toxicity Data:

Oral LD50 (rat): 3,310 - 3,530 mg/kg

- Inhalation LC50 (rat): 11.4 mg/l 4641 ppm / 4 hr
- Dermal LD50: 1,060 mg/kg
- Skin irritation: severe
- Eye irritation (washed eyes): severe
- Eye irritation (unwashed eyes): severe

12. Ecological information

The following properties are ESTIMATED from the components of the preparations.

Potential Toxicity:

Toxicity to fish (LC50): Fish: > 100 mg/l

Toxicity to daphnia (EC50): Daphnia: > 100 mg/l

Persistence and degradability: Not readily biodegradable.

13. Disposal considerations

Discharge, treatment, or disposal may be subject to federal, state, commonwealth, provincial, or local laws. Since emptied containers retain product residue, follow label warnings even after container is emptied.

Material Safety Data Sheet

Revision Date: 08/08/2013

Z17000000388/Version: 2.1

Print Date: 04/08/2015

Page: 6/8

14. Transport information

Not regulated for all modes of transportation.

For more transportation information, go to: www.kodak.com/go/ship.

15. Regulatory information

Notification status

Regulatory List	Notification status
TSCA	All listed
DSL	All listed
NDSL	None listed
EINECS	All listed
ELINCS	None listed
NLP	None listed
AICS	All listed
IECS	All listed
ENCS	All listed
ECI	All listed
NZIoC	All listed
PICCS	All listed

"Not all listed" indicates one or more component is either not on the public Inventory or is subject to exemption requirements. If additional information is needed contact Kodak.

Other regulations

American Conference of Governmental Industrial Hygienists (ACGIH):	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
International Agency for Research on Cancer (IARC):	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Material Safety Data Sheet

Revision Date: 08/08/2013

Z17000000388/Version: 2.1

Print Date: 04/08/2015

Page: 7/8

U.S. National Toxicology Program (NTP):	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
U.S. Occupational Safety and Health Administration (OSHA):	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
California Prop. 65	WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
U.S. - CERCLA/SARA (40 CFR § 302.4 Designation of hazardous substances):	Sodium bisulphite , Ammonium bisulphite , Ammonium acetate
U.S. - CERCLA/SARA - Section 302 (40 CFR § 355 Appendices A and B - The List of Extremely Hazardous Substances and Their Threshold Planning Quantities):	No components of this product are subject to the SARA Section 302 (40 CFR 355) reporting requirements.
U.S. - CERCLA/SARA - Section 313 (40 CFR § 372.65 Toxic Chemical Release Reporting):	Ammonium thiosulphate , Ammonium bisulphite , Ammonium acetate
U.S. - California - 8 CCR Section 339 - Director's List of Hazardous Substances:	Sodium bisulphite , Ammonium bisulphite , Ammonium acetate
U.S. - California - 8 CCR Section 5200-5220 - Specifically Regulated Carcinogens:	No components found on the California Specifically Regulated Carcinogens List.
U.S. - California - 8 CCR Section 5203 Carcinogens:	No components found on the California Section 5203 Carcinogens List.
U.S. - California - 8 CCR Section 5209 Carcinogens:	No components found on the California Section 5209 Carcinogens List.
U.S. - Massachusetts - General Law Chapter 111F (MGL c 111F) - Hazardous Substances Disclosure by Employers (a.k.a. Right to Know Law):	Ammonium thiosulphate , Sodium bisulphite , Ammonium bisulphite , Ammonium acetate
U.S. - Minnesota Employee Right-to-Know (5206.0400, Subpart 5. List of Hazardous Substances):	Sodium bisulphite
U.S. - New Jersey - Worker and Community Right to Know Act (N.J.S.A. 34:5A-1):	Sodium bisulphite , Ammonium bisulphite , Ammonium acetate
U.S. - Pennsylvania - Part XIII. Worker and Community Right-to-Know Act (Chapter 323 Hazardous Substance	Ammonium thiosulphate , Water , Sodium bisulphite , Ammonium

Material Safety Data Sheet

Revision Date: 08/08/2013

Z17000000388/Version: 2.1

Print Date: 04/08/2015

Page: 8/8

List, Appendix A):

bisulphite , Ammonium acetate ,
Acetic acid

16. Other information

The data below reflects current legislative requirements whereas the product in your possession may carry a different version of the label depending on the date of manufacture.

US/Canadian Label Statements:

KODAK EKTACOLOR SMPU P2/RA-2SM KIT, Part A

CONTAINS: Ammonium thiosulphate (7783-18-8) , Sodium bisulphite (7631-90-5) , Ammonium bisulphite (10192-30-0) , Ammonium acetate (631-61-8).

WARNING! MAY BE HARMFUL IF SWALLOWED. CAUSES EYE IRRITATION. DRIED PRODUCT RESIDUE CAN ACT AS A REDUCING AGENT.

Avoid prolonged or repeated breathing of mist or vapour. Avoid contact with eyes, skin, and clothing. Keep container tightly closed to prevent the loss of water. Keep from contact with clothing and other materials. Remove and wash contaminated clothing promptly. Use only with adequate ventilation. Wash thoroughly after handling. **FIRST AID:** If inhaled, remove to fresh air. Get medical attention if symptoms occur. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lens, if worn. Get medical attention. Wash off with soap and water. Get medical attention if symptoms occur. If swallowed, DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control centre immediately. Keep out of reach of children. Do not handle or use until safety precautions in Material Safety Data Sheet (MSDS) have been read and understood. Since emptied containers retain product residue, follow label warnings even after container is emptied. **IN CASE OF FIRE:** Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Flush with plenty of water. **IN CASE OF SPILL:** Absorb spill with vermiculite or other inert material. Collect in a noncombustible container for prompt disposal. Clean surface thoroughly to remove residual contamination. For Large Spills: Flush with plenty of water. Additional Components Include: Water (7732-18-5) .

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment. The information relating to the working solution is for guidance purposes only, and is based on correct mixing and use of the product according to instructions.

R-1, S-2, F-1, C-1